



Product Description

Asian Paints Apex Ultima Advanced Anti Algal Weather Proof is a water-based, modified acrylic smooth emulsion with silicon additives that offers an anti-algal and high performance exterior wall finish.

Performance Features & Benefits

Asian Paints Apex Ultima comes with Colour Stay™ technology, which prevents tarnishing of the paint film and ensures brighter & cleaner shades. Its unique advanced anti algal chemistry ensures that exterior walls are provided with power-packed resistance against algal and fungal growth. It also offers excellent Dirt Pick Up Resistance (DPUR).

Recommended Usage

Asian Paints Apex Ultima is an exterior wall finish that can be applied on various types of exterior cement plasters, asbestos sheets and concrete structures.

It should not be applied on surfaces / substrates that are subjected to continuous seepage or dampness.

Surface Preparation

Freshly Plastered Surfaces: This must be allowed to cure completely.

Cleaning: Ensure that the surface to be painted is free from any loose paint, dust or grease. Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water.

Filling: Surface imperfections such as holes, dents, fine cracks are to be filled using Asian Paints Wall Putty (X3) or a mixture of white cement and fine sand (in the ratio 1:3).

Chalky Surfaces: When the underlying surface exhibits chalkiness, in spite of thorough surface cleaning, use Asian Paints Exterior Sealer (X1).

Application System

Product	Product Code	Thinner	Dilution % (by vol)	Application ¹ Viscosity (sec)	Recoating ² Period (hrs)
Asian Paints Wall Putty (X3) (Optional)	0079	Water	As per requirement to form paste	Paste form	4 hrs
Asian Paints Exterior Wall Primer (X2) Brush, Spray (Mandatory)	0065	Water	🔪 90-110 🔪 40-45	🔪 15-18 🔪 33	4 hrs
Asian Paints Apex Ultima 1st coat Brush, Roller, Spray (Mandatory)	0068	Water	🔪 max 40 🔪 max 40	🔪 35-45 🔪 35-45	4-6 hrs
Asian Paints Apex Ultima 2nd coat Brush, Roller, Spray (Mandatory)	0068	Water	🔪 max 40 🔪 max 40	🔪 35-45 🔪 35-45	4-6 hrs

- ☞ Ensure that horizontal surfaces like top of windows, ledges etc. are painted with 3 coats of Apex Ultima for greater protection.
- ☞ Application of Exterior Wall Primer is mandatory. Not doing so can lead to failure of the paint film.

1. As measured through a Ford cup.

2. Recoat period is quoted for 25°C and 50% Relative Humidity, these may vary under different conditions.





APEX ULTIMA Advanced Anti Algal Weather Proof Emulsion

Technical Data

- a) Coverage**:** On normal masonry surface by brushing:
1 coat: 10.5 – 11.5 sq.mtr/ltr
2 coats: 5 – 6 sq.mtr/ltr
- b) Drying Time:** Surface dry time ~ 30 minutes
- c) Sheen Levels:** 3 – 12 at 60 deg GH
- d) Flash Point**
(IS 101/1987, Part 1, Sec 6): NA
- e) Stability of Thinned Paint:** Use within 24 hrs.
- f) Shelf-life:** 3 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

** Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity.

Precautions

- Kindly refer to the MSDS for Asian Paints Apex Ultima which gives detailed information on safety measures while handling the paint.
- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application.
- Do not over-thin or over-extend the brush.
- Do not use Apcolite Universal Stainers or any other colourants.
- Stir well and strain before use.
- Tinted paints need thorough shaking immediately after tinter addition as well as before use.
- Excessive bird droppings/spitting may affect the performance of the product.

Pack Sizes & Shade Range

Pack size availability:

1 ltr, 4 ltr, 10 ltr, 20 ltr

Shade Range:

Currently available in more than 1200 shades as per the Asian Paints Colour Palette.



Post Application Instructions

For the best performance of the paint, ensure proper washing and cleaning of all algal and fungal growth, if any, at regular intervals of six months.

Safety Features

Non-flammable

Contact us



For more information, visit our website at www.asianpaints.com

For feedback /complaints, write to Marketing Manager - Services, or call



1800-209-5678



No Added Lead,
Mercury, Arsenic &
Chromium

XU

V. NO. 4 | 08/2011

asianpaints

Asian Paints Limited, 6A, Shantinagar,
Santacruz (East), Mumbai - 400 055.