asianpaints



APEX
WEATHER PROOF
EXTERIOR EMULSION

ACE EXTERIOR EMULSION

Featuring

APEX TILE GUARD

WHITES, BEIGES & BROWNS

Rain Drop	L143	Old Lace	0950	Antique White	0940
Bonewhite	0964	Meadow Lark	8499	Talc	0N22
Enlighten-N	4148	Cold Coffee	L129	Spice	0477
Beige-N	0302	Buttercup-N	0336	Barley	0572
Burnt Yellowstone-N	4120	Apricot-N	0501	Light Biscuit-N	0318
Sandstone*	3211	Brandy*	4115	Brownstone*	4234
Tropical Tan*	8455	Copper Leaf*	0523	Old Brick*	8613

Shades are shown for indication purpose only

YELLOWS, ORANGES & RED

Swan Wing	L101	Coral Shell	0951	Twilight Hush	0944
Hearth*	7930	Marigold	7986	Flawless Peach	8011
Raffia*	7929	Fossil	7985	Beach Shack	8603
Autumn Valley	7898	Mango Duet	7977	Palace Lights-N	0N17
Mid Cream	0358	Mango Shake*	7960	Bonny Peach	8610
Morning Dream	7904	Orange Crush*	7959	Lingering Brew	7027
Polka*	7869	Orange Vision*	X110	Terracotta-N*	0427

BLUES, GREENS & GREYS

Sky Mimic	7420	Cashmere-N	3119	Autumn Day	8252
Alliance	1203	Green Whisper	2425	Crusade - N	0684
Bali Blue	8266	Paddy Field	7570	Steel	6142
Summer Sky	7274	Forest Hike	7625	Grey Flannel	8331
Gauguin Blue	7344	Sultry*	9383	Aluminium	8337
Piece of Sky	7304	Green Gold*	0342	Smoke-N	0616
Soothing Sapphire	7326	Mehendi-N*	2361	Stone Path*	8255

LATEST APEX COMBINATIONS

Hushed Hue	7771	Lemon Souffle	7773
Cotton Wool	L104	Steel Grey	0643
Sands of Time	4202	Nut Brown-N*	0419
Apricot Illusion	7979	Sunrise	0526
Aqua Hint	L114	Mystic Dream*	7293
Sporty Yellow+	X104	Pine-N*	0757
Ivory	0315	Milan Red	8101

^{*}Apply 3 coats for good hiding

⁺Available only in Apex

APEX TILE GUARD





APEX TILE GUARD

Asian Paints Apex Tile Guard is a water-based, modified acrylic emulsion specially formulated for clay roof tiles.

Roof tiles face the direct impact of monsoons and UV sunrays, and therefore require special protection. Asian Paints offers Apex Tile Guard, a paint specifically designed for your exterior roof tiles.

It is a high performance water-based paint that forms a protective cover on roof tiles and acts as a shield even in the toughest of conditions. Its unique formulation repels water and provides resistance against algal and fungal growth. The product is available in a wide range of colours as well as a transparent coating, in a rich sheen finish, which offers you an excellent décor solution.

APEX TILE GUARD - DIRECTIONS FOR USE

- Clean the surface thoroughly using a wire brush and remove loose material from the surface. Growths of fungus, algae or moss should be removed by wire brushing and water.
- 2 In case of dents and holes use Asian Paints TruCare Wall Putty or white cement and fine sand in the ratio 1:3
- 3 Apply 2-3 coats of Asian Paints Apex Tile Guard, after diluting 1 litre of Tile Guard with a maximum of 300 ml of water.
- A gap of 4-6 hrs should be maintained between painting two successive coats.
- This product is not recommended for use on glazed, non-porous or very smooth tiles or masonry surfaces.



DIRECTIONS FOR USE

Surface Preparation



Ensure that the surface to be painted is free from loose paint, dust, grease and algae, by vigorous wire brushing and cleaning with water, followed by a coat of an effective bio-wash solution. Asian Paints TruCare BioBlock is recommended as it effectively kills algal and fungal formations and prevents recurrence.



Surface Smoothening/Crack Filling



Walls may have slight irregularities and imperfections such as holes, dents and cracks. Asian Paints TruCare Wall Putty is recommended to level minor undulations and smoothen the wall surface.



Asian Paints SmartCare Crack Seal is recommended for cracks up to 3mm in width. It is a fibre-glass reinforced, ready to use crack filling compound for both interior and exterior masonry surfaces. Larger cracks can be filled by a mixture of white cement and sand (in a ratio of 1:3).



Primer Coat



Before application of the topcoat, it is necessary to apply a coat of an exterior durable primer for better adhesion and to increase the durability of the paint. For fresh surfaces, we



recommend Asian Paints SmartCare Primero, an alkali resistant primer-cum-sealer, specially designed for application on fresh plaster and manufactured sand substrates.



On fully cured plaster surfaces and for re-painting, you can alternatively use Asian Paints TruCare Exterior Wall Primer.



Topcoat

Apply 2-3 coats of Asian Paints Ace/Apex by diluting 1 litre with a maximum of 400 ml of water. Ensure a gap of 4-6 hrs between the coats. Apply a third coat on horizontal surfaces for additional protection.



PAINT APPLICATION PROCESS

APPLICATION	THINNER	DILUTION % (BY VOLUME)	APPLICATION ¹ VISCOSITY (SEC)	RECOATING PERIOD (HOURS)	
STEP 1 ASIAN PAINTS TRUCARE WALL PUTTY (OPTIONAL)	♦ WATER	BASED ON REQUIREMENT TO FORM PASTE	PASTE FORM	4 HRS	
STEP 2 TRUCARE EXTERIOR WALL PRIMER BRUSH / ROLLER / SPRAY	WATER	BRUSH 90 - 110 ROLLER 90 - 110 SPRAY 40 - 45	BRUSH 15 - 18 SPRAY 33	4 HRS	

BE PAINTED WITH 3 COATS OF ACE FOR GREATER PROTECTION

APPLICATION OF PRIMER IS MANDATORY

STEP 3 FIRST COAT EXTERIOR EMULSION BRUSH / ROLLER / SPRAY	♦ WATER	BRUSH 75 ROLLER 75 SPRAY 75	BRUSH 20 - 25 SPRAY 20 - 25	4 - 6 HRS
STEP 4				

STEP 4
SECOND COAT
EXTERIOR EMULSION
BRUSH / ROLLER / SPRAY

WATER

BRUSH 75
ROLLER MAX 75
SPRAY 75

BRUSH 20 - 25
SPRAY 20 - 25

4 - 6 HRS



Asian Paints Apex Weather Proof Exterior Emulsion is a water-based paint which gives excellent protection for exterior walls against algal attack as well as UV and alkali degradation.



Asian Paints Ace Exterior Emulsion is an economy emulsion suitable for dry or moderately humid climatic conditions, offering significantly beter life and performance compared to cement paint.





* Asian Paints Ezypainting Service

Painting your home is exciting. With Asian Paints Ezy Painting service, re-imagine your house as a huge canvas that you can choose to paint and make it look the way you wish.

But choosing the correct colours, products, and painters can be a huge task. That's where we come in with our aim to make painting a great experience!

Our Supervisors will take care of all your wall painting, wood finishing and waterproofing needs.

- Expert Supervision
- Wallpapers and Textured Finishes
- Wood Solution
- Waterproofing Solutions

For Professional Painting Services Call 18002095678



For more information log on to www.asianpaints.com, or call us at 1800-209-5678.