

PRODUCT CODE AD019878

FlexEasy

Asian Paints FlexEasy is a low viscosity cyanoacrylate which is designed for flex bonding and for the assembly of difficult to-bond materials which require uniform stress distribution and strong tension and/or shear strength. The product provides rapid bonding of a wide range of materials, including metals, plastics and elastomers.



PRODUCT BENEFITS

Fast Cure

Full functional strength is developed in a relatively short time.

High Strength

Product has a superior strength.

LEAD FREE* GUARANTEE



* All Asian Paints products contain no added Lead, Mercury, Arsenic or Chromium from April 2008.


PRODUCT FEATURES

AVAILABLE PACKS




PRODUCT APPEARANCE

TRANSPARENT



5 - 30
SECONDS

RECOMMENDED USAGE



FLEX



PLASTICS



RUBBER



METAL

HOW TO APPLY

PRE-APPLICATION STEPS

ROUGHEN, DRY AND CLEAN SURFACES TO BE BONDED



Clean and dry surfaces to be bonded.

APPLICATION PROCESS

STEP 1



Sand the substrate with emery paper.

STEP 2




Twist the cap to open nozzle. Tilt bottle and squeeze to dispense adhesives.

STEP 3



Apply adhesive on the corners of the frame.

STEP 4



After use, tap the bottle to allow the adhesive in nozzle to settle down in the bottle before replacing the cap. Store in a cool, dry place in an upright position.

ADDITIONAL INFORMATION

SAFETY FEATURES

- Store product in the unopened bottle in a dry location.
- Keep out of reach of children and away from eatables.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Do not pour leftover adhesive down the drain or in water courses.

TECHNICAL DETAILS

- Shelf Life: 9 months from the date of manufacture
- Storage Temperature: 18 deg. C to 25 deg. C

PRECAUTIONS

- Avoid using more than the prescribed quantity of adhesive, as the thick layer between the bonding surfaces may affect the bond strength