

PRODUCT CODE 3058

TruGrip Masking Tapes

Asian Paints TruGrip Masking Tapes are designed to be used in a wide range of painting, brushing and spraying applications. They are suitable for masking of variety of substrates and for wood work.

Asian Paints TruGrip Masking Tapes help you achieve the right finish for your surfaces.



PRODUCT BENEFITS

- **Single solution to both painters & carpenters**
- **Optimum combination of peel strength and sheer strength**
- **No paint seepage, no residue on substrate upon removal**

asianpaints

LEAD FREE* GUARANTEE



* All Asian Paints products contain no added Lead, Mercury, Arsenic or Chromium from April 2008.

PRODUCT FEATURES


PRODUCT APPEARANCE

OPAQUE

SETTING TIME



RECOMMENDED USAGE



CARPENTRY

Various wood substrates



STENCIL



PAINTING

FOR PAINTING

PRE-APPLICATION STEPS


ROUGHEN, DRY AND CLEAN SURFACES TO BE BONDED



Clean and dry surface where the tape has to be used


APPLICATION PROCESS

STEP 1



Apply the tape on the edges of the surface to be painted so that the tape acts as a border for the surface.

STEP 2



After painting, gently remove the tape and dispose.

FOR CARPENTRY

PRE-APPLICATION STEPS

ROUGHEN, DRY AND CLEAN SURFACES TO BE BONDED



Clean and dry surface where the tape has to be used


APPLICATION PROCESS

STEP 1




Apply the adhesive on the surfaces to be held together.

STEP 2



Once stuck together, secure both the substrates with masking tape. Optionally, place a heavy object on the surface.

STEP 3



After drying, gently remove the tape and dispose.

ADDITIONAL INFORMATION

SAFETY FEATURES

- Store the product in a cool and dry place.
- Keep out of reach of children and away from eatables.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Do not pour leftover tapes down the drain or in water courses.

TECHNICAL DETAILS

- Form: XXX
- Storage Temperature: 18 deg. C to 25 deg. C