

PRODUCT CODE 5060

TruGrip Super Masking Tapes

Asian paints Trugrip Super Masking Tapes are specially designed to be used in wide range of high strength applications. They are suitable for clamping during wood work and for masking a variety of substrates.



PRODUCT BENEFITS

- **High strength for clamping**
- **High initial tackiness**
- **No seepage, assured quality and no residue on removal from the substrates**


LEAD FREE* GUARANTEE


* All Asian Paints products contain no added Lead, Mercury, Arsenic or Chromium from April 2008.

PRODUCT FEATURES

PRODUCT APPEARANCE

OPAQUE

SETTING TIME



RECOMMENDED USAGE


CARPENTRY

Various wood substrates


STENCIL

PAINTING

FOR CARPENTRY

PRE-APPLICATION STEPS

ROUGHEN, DRY AND CLEAN SURFACES TO BE BONDED


Clean and dry surface where the tape has to be used


APPLICATION PROCESS

STEP 1


Apply the adhesive on the surfaces to be held together.

STEP 2


Once stuck together, secure both the substrates with masking tape. Optionally, place a heavy object on the surface.

STEP 3


After drying, gently remove the tape and dispose.

FOR PAINTING

PRE-APPLICATION STEPS

ROUGHEN, DRY AND CLEAN SURFACES TO BE BONDED


Clean and dry surface where the tape has to be used

APPLICATION PROCESS

STEP 1


Apply the tape on the edges of the surface to be painted so that the tape acts as a border for the surface.

STEP 2


After painting, gently remove the tape and dispose.

ADDITIONAL INFORMATION

SAFETY FEATURES

- Store the product in a cool and dry place.
- Keep out of reach of children and away from eatables.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Do not pour leftover tapes down the drain or in water courses.

TECHNICAL DETAILS

- The product must be protected from dust, heat, moisture and direct sunlight.
- Storage Temperature: 18°C to 25°C