

## PRODUCT FEATURES & BENEFITS

Asian Paints Classique Premium Acrylic Interior Emulsion provides a rich low sheen finish to your wall and it is available in over 5000 shades.

Asian Paints Classique Premium Acrylic Interior Emulsion provides a rich and smooth finish for interior walls. It's composition imparts excellent durability to the paint film, gives your walls that "just painted" look year after year. Asian Paints Classique Premium Acrylic Interior Emulsion is washable and most stains can be removed easily by sponging with a mild soap solution. The paint film is also fungus and mildew resistant. We do not add Lead, Mercury, Arsenic or Chromium and other raw materials containing heavy metals in the manufacturing process.

Asian Paints Classique Premium Acrylic Interior Emulsion is an interior wall finish that can be applied on all types of smooth plasters, false ceilings, asbestos sheets, concrete etc.



### SURFACE



INTERIOR

### AVAILABLE PACKS



Shelf life: 3 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

### COLOURS AVAILABLE

5000+\*



Currently Available in Pure Brilliant White and more than 5000 colours as per Asian Paints Colour Palette & other colour cards

### FINISH



✓ SMOOTH  
Refer to sheen levels in technical details

### COVERAGE

On normal masonry surface after brushing/roller



\*\*Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity.

## HOW TO APPLY

**Cleaning:** Ensure that the surface to be painted is free from any loose paint, dust or grease. Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water.

**Filling:** Minor surface imperfections such as holes, dents and cracks up to 3mm are to be filled with SmartCare Crack seal Asian Paints AP Kote Wall Putty or Skim Kote can be used to level the surface. Large holes to be filled with only by using mixture of white cement & fine sand (in the ratio of 1:3)

Freshly-plastered surfaces must be allowed to cure completely and pH should be between 7-9 at the time of application.

Apply top coats as follows.

### PRE PAINTING STEPS



**PLASTER** New masonry surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces.



**FILLING FOR CRACKS** For filling cracks upto 3mm use Asian Paints SmartCare Crack Seal.



**CLEANING** Surface should be free from any loose paint, dust or grease. Growths of fungus, algae or moss should be removed by wire brushing and water. In case of areas having excessive dampness use Asian Paints SmartCare DampBlock to limit further dampness. When the underlying surface exhibits chalkiness, in spite of thorough surface cleaning, use Asian Paints SmartCare Exterior Sealer.



**FILLING FOR HOLES & DENTS** In case of dents and holes use Asian Paints Wall Putty or white cement and fine sand in the ratio 1:3



**For exterior surfaces or substrates that are subjected to continuous seepage or dampness, kindly use Asian Paints SmartCare DampProof, before the top coat application.**

### PAINT APPLICATION PROCESS

| Product  | Product Code | Thinner | Dilution % (by vol) | Application Viscosity | Re coating* Period (hrs) |
|--|--------------|---------|---------------------|-----------------------|--------------------------|
| Sand the surface with Emery Paper 180 & wipe clean<br>Asian Paints Acrylic Wall Filler Brush, Roller                                     | AP 04        | Water   | 35 - 45             | N/A                   | 3 - 4 hrs                |
| Asian Paints AP Kote Wall Putty Putty Knife  | AP 33        | N/A     | As Required         | N/A                   | 8 - 12 hrs               |
| Sand the surface with Emery Paper 180 & wipe clean<br>Asian Paints Acrylic Wall Filler Brush, Roller                                     | AP 04        | Water   | 35 - 45             | N/A                   | 3 - 4 hrs                |
| Sand the surface with Emery Paper 320 & wipe clean<br>Asian Paints Classique Premium Acrylic Interior Emulsion 1st Coat<br>Brush, Roller | AP 01        | Water   | 35 - 40             | 50 - 60 KU            | 3 - 4 hrs                |
| Asian Paints Classique Premium Acrylic Interior Emulsion 2nd Coat<br>Brush, Roller   | AP 01        | Water   | 25 - 30             | 55 - 65 KU            | 3 - 4 hrs                |

\* Re-coat period is quoted for 25<sup>0</sup> C and 50% Relative Humidity. These may vary under different conditions

\* For best results and to avoid patchiness (lime blooming), Asian Paints Exterior Sealer is recommended under the following conditions:

- When the underlying surface exhibits chalkiness in spite of thorough surface cleaning
- In areas where the water table is high, leading to excessive seepages/dampness
- In coastal high humid areas.

## ADDITIONAL INFORMATION

### TECHNICAL DATA

|  |   |  |
|--|---|--|
| a) Coverage **                                 | : | On smooth primed masonry surface by brushing<br>1st Coat: 15-20 sq.mtr/ltr (160-215 sq.ft./ltr)<br>2nd Coat: 8-12 sq.mtr/ltr (85-130 sq.ft./ltr) |
| b) Drying Time                                 | : | Surface dry time 10-15 minutes   |
| c) Gloss Levels / Sheen                        | : | 1-6 at 60 deg GH   |
| d) Flash Point<br>(IS 101/1987, Part 1, Sec 6) | : | N/A  |
| e) Stability of Thinned Paint                  | : | Use within 24 hrs  |
| f) Shelf - life                                | : | 3 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.                             |

\*\* Actual coverage may vary from the quoted coverage due to factors such as methods & condition of application and surface roughness  
Deep bright colours may require additional coat of paint.

### PRECAUTIONS

- Kindly refer to the MSDS of Asian Paints Classique Premium Acrylic Interior Emulsion which gives detailed information of safety measures while handling the paint.
- Do not apply when ambient temperature is less than 10<sup>0</sup>C or If the temperature might drop to this level within 4 hours application.
- Do not over thin or overextend the brush.
- Do not use Asian Paints Universal Strainers or any other colorants after tinting without an approval from the technical division of Asian Paints.
- Ensure that horizontal surfaces like top of windows, edges etc. are painted with 3 coats for greater protection.
- Tinted paints need thorough shaking immediately after thinner addition as well as before use
- Stir well as before use.

### PACK SIZES & SHADES RANGE

Pack size availability:

1 ltr, 4 ltr, 10 ltr, 18 ltr, 20 ltr.

### SHADE RANGE

Currently Available in Pure Brilliant White and more than 5000 colours as per Asian Paints Colour Palette & other colour cards

### POST APPLICATION INSTRUCTIONS

A freshly prepared surface should be allowed a drying time of minimum 2 weeks for proper film formation. Subsequently to remove stains, use a sponge and clean with mild detergent solution and wipe the surface. Remove stains within 24hours to ensure best results.

### SAFETY FEATURES

- Non-Flammable
- Kindly refer to the MSDS for Asian Paints Classique Premium Acrylic Interior Emulsion which gives detailed information on safety measures while handling the paint.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- Keep out of reach of children and away from food, drink.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Do not pour leftover paint down the drain or in water courses.
- In the event of spills, contain spillage using sand or earth.
- Safety Data Sheet available for professional user on request.
- No added Lead, Mercury or Chromium compounds