

# BRIGHT ALUMINIUM

## PRODUCT DESCRIPTION

High quality Bright Aluminium Paint based on treated oil varnish medium and incorporating high luster flake aluminum with extremely durable and exceptional water resistance properties.

## AREAS OF APPLICATION

For interior and exterior surfaces where durable and brilliant finishes are required such as Storage tanks, piping railings and galvanized roofing sheets etc.,

## PRODUCT INFORMATION

Pack size	4 liter, 1 liter, 500ml, and 200ml	
Shade / Colour range	Metallic Aluminium	
Method of Application	Brush, or Spray	

## TECHNICAL INFORMATION/ DATA

Thinner	Asian Paints Mineral Turpentine.
Thinning ratio (by vol.)	Supplied ready for use and if necessary add up to 5-10% with Asian Paints Mineral Turpentine.
Spreading Rate	Approximately 15-20 sq. mt / per liter
Drying time at 30 <sup>°</sup> C	
Surface Drying	3 hour
Hard Drying	10 – 12 hours
Recoating Time	After 16 hours

### SURFACE PREPARATION

#### Wood Work

Sand paper thoroughly. Clean down, apply one coat of Asian Paints Aluminium Wood Primer before applying Bright Aluminum Paint.

#### Iron & Steel

Remove scale and surface rust by chipping and wire brushing. Clean down and apply a coat of Asian Paints Zinc Phosphate Primer for better results.

#### **Galvanized Iron**

Wash down with Asian Paints Mineral Turpentine, allow drying & apply a coat of Metacare Etch Primer before application of Asian Paints Bright Aluminium Paint.

#### Aluminium & Aluminium Alloys

Wash down with Asian Paints Mineral Turpentine. Rub down with steel wool or abrasive paper. Clean and apply one coat of Metacare Etch Primer before applying Bright Aluminium.

## SAFETY INFORMATION AND PRECAUTIONS

- Ensure good ventilation between application and drying.
- If splashes enter eyes, wash with plenty of water.
- Keep out of reach of children.
- Store and keep away from heat and flame.

## CONTACT US

For further information, or if you have any queries about using this product, please contact our office at:

Asian Paints (Lanka) Ltd.

81, Koralawella Road, Moratuwa.

Ph: 011-2658621-4	Website: www.asianpaints.com
Fax: 011-2658200	Email id: contact@asianpaints.lk

#### DISCLAIMER

Although the facts and suggestion in this publication are based on our own research and are believed reliable, we cannot assume any responsibility for performance or results obtained through the use of our products herein described, nor do we accept any liability for loss or damages directly caused by our products. The user is held to check the quality, safety and all other properties of our product prior to use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.