



## ARCHITECTURAL COATINGS

**ASIAN PAINTS  
WATER BASE  
EXTERIOR TOP COAT**

Water-Based wood coating for exterior use

## PRODUCT FEATURES &amp; BENEFITS

- Easy Application.
- Quick drying.
- Superior exterior durability.
- UV protection.
- Algae & fungal protection.
- Flexible paint film.

## AREAS OF APPLICATION

Suitable for all types of exterior wooden surfaces and furniture.

## PRODUCT INFORMATION

Shade / Colour range	Clear
Gloss level	30 & 60 @ 60 deg
Packing	500ml, 1 liter and 4 liter.
Method of Application	Brush or spray.

## TECHNICAL INFORMATION/ DATA

Viscosity of supply	Ready to use.
Thinner	Municipal/Potable Water.
Covering Capacity	On smooth sanded wooden surface by Brushing + Rolling 8 – 12 SQ. m per coat. <small>**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. Please purchase appropriate amount for the job.</small>
Thinning	20% max
Stability of thinned paint	To be used within 24 hours.
Shelf Life	24 Months from date of manufacture in original tightly closed container away from direct sunlight and extensive heat.
Drying time at 30 °C	
Touch Dry	60 min
Hard dry / Recoatability	3 hours



Water-Based wood coating for exterior use

## ARCHITECTURAL COATINGS

### ASIAN PAINTS WATER BASE EXTERIOR TOP COAT

#### SURFACE PREPARATION

Wood must be well dry (less than 12% humidity). Clean well the surface removing all traces of grease, waxes and resins. Perform sanding with 150 grit paper for softwoods and 180 grit paper for hardwoods

1. Sand the wooden surface along the grains using sand paper No.180, and then 320 or 400. Wipe surface to clean off loose dust particles.
2. If the surface has dents, apply Asian Paints Aquadur Dent Filler with a putty knife over the dented area.
3. To colour, Apply Asian Paints Water base Wood stains. Allow to dry for 30 to 120 minutes.
4. Keep light sanding between coats with sand paper No. 400.
5. Apply 2 coats of Asian Paints water base Exterior top coat by brush or roller.
6. Mix Matt and Glossy finishes for desired level of sheen.
7. Recoat period is quoted for 30°C and 75% relative humidity; these may vary under different conditions.
8. Spraying air pressure 2.2 - 2.8 Kgs/sq.cm.

#### PRECAUTIONS

- a) For optimum performance, Asian Paints Water base Exterior top coat must be applied at a temperature between 20°C and 40°C and humidity not above 75%.
- b) Apply WB wood preservative coat for better protection.
- c) Do not over-thin and mix according to recommended ratios.
- d) Stir well and strain before use.

#### POST PAINTING CARE

- a) For removing stains on tiles and metal surfaces, apply NC Thinner on the surface and wipe clean.
- b) If stains are difficult to remove, scrapping can be done after applying NC thinner on the stained area.
- c) Precautions need to be taken while spraying / brushing, like masking of adjoining areas with suitable material, as the stains may be difficult to remove if present on wood or coated wooden and wall surfaces.



Water-Based wood coating for exterior use

Product Data Sheet  
**ARCHITECTURAL COATINGS**

**ASIAN PAINTS  
WATER BASE  
EXTERIOR TOP COAT**

**SAFETY FEATURES**

- Kindly refer to the MSDS for Asian Paints Water base Exterior top coat, Gloss and Matt, which gives detailed information on safety measures while handling the paint.
- Store the product at ambient conditions in well ventilated locations and away from source of ignition and fire.
- Use protective equipment like rubber/polyurethane gloves, safety goggles/glasses, and face mask while handling the paint.
- Avoid eye and skin contact. In both cases wash with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not inhale or ingest. In case of inhalation move to fresh air and seek medical attention if symptoms persist in both cases.
- Do not dispose empty cans in any drain or land filling.
- No added Lead, Mercury or Chromium compounds.

**CONTACT US**

For further information, or if you have any queries about using this product, please contact our office at:

Asian Paints (Lanka) Ltd.  
81, Koralawella Road, Moratuwa.

Ph: 011-2658621-4  
Fax: 011-2658200

Website: [www.asianpaints.com](http://www.asianpaints.com)  
Email id: [contact.lanka@asianpaints.lk](mailto:contact.lanka@asianpaints.lk)

**DISCLAIMER**

Although the facts and suggestion in this publication are based on our own research and are believed reliable, we cannot assume any responsibility for performance or results obtained through the use of our products herein described, nor do we accept any liability for loss or damages directly caused by our products. The user is held to check the quality, safety and all other properties of our product prior to use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.