

Asian Paints Woodtech Genie Polish Clear

PRODUCT CODE: 5485

WOODTECH GENIE POLISH BENEFITS



GOOD GLOSS

Apply Genie Polish to get a good gloss each time



EASE OF TONE MATCHING

Mix coloured powder or chalk powder directly into Genie Polish to get a uniform tone



NON-YELLOWING

Does not yellow, retains the new look of the furniture



HEALTH SAFE

Does not cause skin irritation or numbing of fingers



PRODUCT FEATURES

DURABILITY



BEST IN CLASS

HIGH

✓ MODERATE

LOW

COLOURS AVAILABLE

Clear

AVAILABLE PACKS



200ml



500ml




1ltr



5lts

COVERAGE

240-260 sqft/ltr/coat



FINISH



MATT SEMI GLOSS **GLOSS** HIGH GLOSS

HOW TO APPLY

PRE PAINTING STEPS



Sand the wooden surface along the grains using sand paper No.180, and then 320 or 400.Wipe surface to clean off loose dust particles.

PAINT APPLICATION PROCESS

APPLICATION	PRODUCT CODE	THINNER	DILUTION % (BY VOL)	VISCOSITY (SEC)	RECOATING PERIOD (Min)
STEP 1 ASIAN PAINTS WOODTECH GENIE POLISH 1ST COAT RAGGING	5485	With Potable Water	5 -10% (If Required)	11-17	10
STEP 2 ASIAN PAINTS WOODTECH GENIE POLISH 2ND COAT RAGGING	5485	With Potable Water	5 -10% (If Required)	11-17	10
STEP 3 APPLY COATS AFTER COATS BY RAGGING TILL DESIRED FILLING IS OBSERVED.					

Note: 1.Shake the bottle of Woodtech Genie Polish thoroughly before use.
2.Light sanding can be carried out using emery paper 320 or 400 in-between coats if required.
3.For overcoating with any Topcoat like Touchwood or Melamylne, allow the polish to dry for at least 3-4 hrs.
4.The containers should be tightly closed after use.
5.Recoat period is quoted for 30°C and 75% relative humidity; these may vary under different conditions.
6.Viscosity as measured through a Ford cup B4 at 30°C.

Asian Paints Woodtech Genie Polish Clear



ADDITIONAL INFORMATION

POST PAINTING CARE

- ◆ For removing stains from tiles and metal surfaces, apply NC thinner on the surface and wipe clean.
- ◆ If stains are difficult to remove, scrapping can be done after applying NC thinner on the stained area.
- ◆ Precautions need to be taken while filling, like masking of adjoining areas with suitable material, as the stains may be difficult to remove if present on wood or coated wooden and wall surfaces.

TECHNICAL DETAILS

- a. Drying time: Dry to touch time ~ 15 minutes, tack free time ~ 45 Minutes.
- b. Flash point: (IS 101/1987, Part 1, Sec 6) : above 35°C (95° F).
- c. Stability of thinned paint: Not Applicable.
- d. Shelf Life: 12 Months from date of manufacture in original tightly closed container stored away from direct sunlight and extensive heat.

PRECAUTIONS

- ◆ For optimum performance, Asian Paints Woodtech Genie Polish must be applied at a temperature between 20°C and 40°C and humidity not above 75%.
- ◆ Shake well before use.

SAFETY FEATURES

- ◆ Kindly refer to the MSDS for Asian Paints Woodtech Genie Polish which gives detailed information on safety measures while handling the polish.
- ◆ Store the product at ambient conditions in well ventilated locations and away from source of ignition and fire.
- ◆ Use protective equipment like rubber/polyurethane gloves, safety goggles/glasses, face mask while handling the polish.
- ◆ Avoid eye and skin contact. In both cases wash with soap and plenty of water. Get Medical attention if irritation develops or persists.
- ◆ Do not inhale or ingest. In case of inhalation move to fresh air and seek medical attention if symptoms persist in both cases.
- ◆ Dispose in land filling. Do not dispose in any drain or land filling
No added Lead, Mercury or Chromium compounds.