

# Asian Paints WoodTech Touchwood Interior

PRODUCT CODE: 0562




## WOODTECH TOUCHWOOD BENEFITS



### EASY APPLICATION

WoodTech Touchwood can be applied on wood quickly, simply by using a brush.



### SELF SEALING

WoodTech Touchwood does not require a separate sealer coat to be applied. The same material can be applied as undercoat and topcoat.



### HARDNESS

WoodTech Touchwood Interior provides better hardness and protection to wood compared to the local French polish.

## PRODUCT FEATURES

### DURABILITY



EXCELLENT  
HIGH  
✓ MODERATE  
LOW

### COVERAGE

On smooth sanded wooden surface by Spraying :  
90-110 sq.ft./ltr/coat



### COLOURS AVAILABLE

## Clear & Oak Yellow

Range of 9 attractive Translucent Asian Paints WoodTech Wood Stains & 6 Attractive WoodTech Aquadur Waterbased Wood Stains available to add/change colour.



### FINISH

SILK MATT SEMI GLOSS **GLOSSY** HIGH GLOSS

### AVAILABLE PACKS



Woodtech Touchwood Wood Finish Clear Glossy (0562) - 200 ml, 500ml 1lt, 4lts  
Woodtech Touchwood Touchwood Wood Finish Oak Yellow Glossy (0562) - 200ml, 500 ml, 1lt, 4lts

\* Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness.

## HOW TO APPLY

### PRE PAINTING STEPS



1. Sand the wooden surface along the grains using sand paper No. 180, and then 320 or 400. Wipe surface to clean off loose dust particles.



2. If the surface has dents, apply Aquadur Dent Filler with a putty knife over the dented area.



3. To colour, Apply WoodTech Wood stains or Aquadur Wood stain by Ragging. Allow to dry for 30 to 120 minutes.

### PAINT APPLICATION PROCESS

APPLICATION	PRODUCT CODE	THINNER	DILUTION % (BY VOL)	VISCOSITY (SEC)	RECOATING PERIOD (HRS)
STEP 1 WOODTECH TOUCHWOOD GLOSSY 1ST COAT SPRAY/BRUSH	0562	MINERAL TURPENTINE	SPRAY : 20-25 ; BRUSH : 0-5	SPRAY : 20-25 SECS ; BRUSH : 30-55	24 HRS
<b>SANDING</b> Sand the surface with Sand paper 320 or 400 and wipe clean					
STEP 2 WOODTECH TOUCHWOOD GLOSSY 2ND COAT SPRAY/BRUSH	0562	MINERAL TURPENTINE	SPRAY : 20-25 ; BRUSH : 0-5	SPRAY : 20-25 SECS ; BRUSH : 30-55	24 HRS
<b>SANDING</b> ( Apply 3rd Coat if required after sanding with Sand Paper no. 320 / 400 and wipe clean )					

- Note: 1. If required, apply Asian Paints Woodtech Wood Stain by ragging on sanded wooden surface and allow 30 minutes of drying time.  
2. Do not store Asian paints Woodtech Touchwood Interior/Exterior in a half filled container to avoid skin formation. Transfer container to a smaller container so as to leave no air gap.  
3. Take care to cap the container tightly after use.  
4. Asian Paints Woodtech wood stains should not be mixed with Asian Paints Woodtech Touchwood  
5. Mix Matt and Glossy finishes for desired level of sheen.  
6. Asian Paints Woodtech Touchwood must not be polluted with oil, varnish or the like and must not be sanded with steel wool between coats.  
7. Recoat period is quoted for 30°C and 75% relative humidity, these may vary under different conditions.  
8. Recoat period is quoted for 30°C and 75% relative humidity, these may vary under different conditions.  
9. Spraying air pressure 2.2 to 2.8 Kgs/sq.cm.  
10. Viscosity as measured through a Ford cup B4 at 30°C.

# Asian Paints WoodTech Touchwood Interior



## HOW TO CHOOSE COLOUR



WOODSTAIN FANDECK



AQUADUR WOOD STAINS SHADE CARD

## ADDITIONAL INFORMATION

### POST PAINTING CARE

- ◆ For removing stains on tiles and metal surfaces, apply NC Thinner on the surface and wipe clean.
- ◆ If stains are difficult to remove, scrapping can be done after applying NC thinner on the stained area.
- ◆ Precautions need to be taken while spraying / brushing, like masking of adjoining areas with suitable material, as the stains may be difficult to remove if present on wood or coated wooden and wall surfaces.

### TECHNICAL DETAILS

- Drying time: Surface dry time 60 minutes.  
Tack Free time 4 hrs.
- Gloss levels: 80% minimum (Glossy) and 15-25% (Matt) on coated wooden panel at 60° Gloss Head.
- Flash point (IS 101/1987, Part 1, Sec 6): Above 30°C (86°F)
- Stability of thinned paint: To be used within 24 hours
- Shelf Life: 3 years from date of manufacture in original tightly closed container away from direct sunlight and extensive heat.

### PRECAUTIONS

- ◆ For optimum performance, Asian Paints Woodtech Touchwood must be applied at a temperature between 20°C and 40°C and humidity not above 75%
- ◆ Do not over-thin and mix according to recommended ratios
- ◆ Stir well and strain before use.

### SAFETY FEATURES

- ◆ Kindly refer to the MSDS for Asian Paints Woodtech Touchwood which gives detailed information on safety measures while handling the paint.
- ◆ Store the product at ambient conditions in well ventilated locations and away from source of ignition and fire
- ◆ Use protective equipment like rubber/polyurathene gloves, safety goggles/glasses, face mask while handling the paint
- ◆ Avoid eye and skin contact. In both cases wash with soap and plenty of water. Get medical attention if irritation develops or persists.
- ◆ Do not inhale or ingest. In case of inhalation move to fresh air and seek medical attention if symptoms persist in both cases
- ◆ Dispose in land filling. Do not dispose in any drain or land filling
- ◆ No added Lead, Mercury or Chromium compounds
- ◆ Flammable