

Asian Paints WoodTech Wood Stain



PRODUCT CODE: 0556

WOODTECH WOOD STAIN BENEFITS



EASY APPLICATION

WoodTech Wood Stain can be easily applied with a muslin cloth



Exclusive shades

Asian Paints WoodTech Wood stains offer 9 attractive shades

PRODUCT FEATURES

DURABILITY



BEST IN CLASS

HIGH

✓ MODERATE

LOW

COVERAGE




On smooth sanded wooden surface by Spraying
60-70 sq.ft/ltr/Coat**

* Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness.

COLOURS AVAILABLE

Teak, Charcoal, walnut, red brown, red, green, wenge, oak yellow, Rose wood



FINISH

NA

AVAILABLE PACKS



Woodtech Wood Stain (0556)- 100ml, 500ml, 1Ltr, 5Ltr

HOW TO APPLY

PRE PAINTING STEPS



1. Sand the wooden surface along the grains using sand paper No. 180, and then 320 or 400. Wipe surface to clean off loose dust particles.

PAINT APPLICATION PROCESS

APPLICATION	PRODUCT CODE	THINNER	DILUTION % (BY VOL)	VISCOSITY (SEC)	RECOATING PERIOD (HRS)
STEP 1 APPLY WOODTECH WOOD STAIN SPRAY / RAGGING	556	Nil	Nil	Nil	30 minutes

Note:1. Depending on the shade intensity desired, the number of coats can be varied. Give an interval of 5 - 10 minutes between any two coats

- Do not sand the stain coat.
- You can intermix WoodTech wood stains to create a new shade.
- WoodTech wood stains can be mixed with Melamylne Sealer or finish coats of Wood tech Melamylne, WoodTech Melamylne Gold Clear up to 20% by Volume. Allow the stain coat to dry for 5-6 Hrs before sanding for the subsequent coat application.
- Do not mix Asian paints WoodTech Wood Stains with Asian paints WoodTech TouchWood Interior and Asian Paints WoodTech PU Interior.
- For lighter shades, Asian paints WoodTech wood stains can be diluted with NC thinner or Thinner T-124 just before application. Only required shade should be diluted at a time.
- Surfaces stained with Asian Paints WoodTech Wood stains must always be coated with a coat of Asian Paints WoodTech Melamylne, Asian Paints WoodTech Melamylne Gold Clear, Asian Paints WoodTech Touchwood Interior and Asian Paints WoodTech PU Interior.
- Recoat period is quoted for 30°C and 75% relative humidity, these may vary under different conditions.
- Spraying air pressure 2.2 to 2.8 Kgs/sq. cm.
- Viscosity as measured through a Ford cup B4 at 30°C.

Asian Paints WoodTech Wood Stain



HOW TO CHOOSE COLOUR



WOODSTAIN FANDECK



AQUADUR WOOD STAINS SHADE CARD

ADDITIONAL INFORMATION

POST PAINTING CARE

- ◆ For removing stains on tiles and metal surfaces, apply NC Thinner on the surface and wipe clean.
- ◆ If stains are difficult to remove, scrapping can be done after applying NC thinner on the stained area.
- ◆ Precautions need to be taken while spraying / brushing, like masking of adjoining areas with suitable material, as the stains may be difficult to remove if present on wood or coated wooden and wall surfaces.

TECHNICAL DETAILS

- Drying time: Surface dry time 15 minutes
- Gloss levels: NA
- Flash point (IS 101/1987, Part 1, Sec 6): Above 20°C (68°F)
- Stability of thinned paint: NA
- Shelf Life: 3 years from date of manufacture in original tightly closed container away from direct sunlight and extensive heat.

PRECAUTIONS

- ◆ For optimum performance, Asian Paints Woodtech Wood Stains must be applied at a temperature between 20°C and 40°C and humidity not above 75%
- ◆ Do not over-thin and mix according to recommended ratios
- ◆ Stir well and strain before use.

SAFETY FEATURES

- ◆ Kindly refer to the MSDS for Asian Paints Woodtech Wood Stains which gives detailed information on safety measures while handling the paint.
- ◆ Store the product at ambient conditions in well ventilated locations and away from source of ignition and fire
- ◆ Use protective equipment like rubber/polyurathene gloves, safety goggles/glasses, face mask while handling the paint
- ◆ Avoid eye and skin contact. In both cases wash with soap and plenty of water. Get medical attention if irritation develops or persists.
- ◆ Do not inhale or ingest. In case of inhalation move to fresh air and seek medical attention if symptoms persist in both cases
- ◆ Dispose in land filling. Do not dispose in any drain or land filling
- ◆ No added Lead, Mercury or Chromium compounds
- ◆ Flammable